

912843 低浓度过酒软管 VACUPRESS

ENO PHF

层塑胶增强 PVC-PHF 软管，内嵌镀锌钢丝螺旋、聚酯纤维层加强，用于抽吸和输送食品液体、浓度低于 28% 的酒及含酒精液体。



Two-layer plasticized PVC-PHF hose with embedded galvanised steel spiral with polyester yarn reinforcement, for suction and liquids, wine and alcoholic food liquids up to 28%.delivery of food

商品详情

| | |
|------------------------------|-------------------------------|
| 表面平滑度 SMOOTH SURFACE | ***** |
| 柔韧性能 FLEXIBILITY | ***** |
| 耐磨性能 ABRASION RESISTANCE | ISO 4649:<160 mm ³ |
| 适用温度范围 TEMPERATURE RANGE | -25°C + 60°C |
| 抗化学物质 CHEMICAL RESISTANCE | tabella PVC |
| 抗压性能 CRUSHING RESISTANCE | *** |
| 不含酚酞酯 PHTHALATE FREE | PHF ***** |

符合 CE1935/2004 标准和 UE10/2011 标准规定接触食品的介质需要通过在温度 40°C 分别对 A B C 三种模拟液体进行 24 小时的测试。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

| 内径 ID Inc | 内径 ID mm | 外径 OD mm | 重量 WEIGHT g/m | 弯曲半径 BENDING RADIUS m/m | 工作压力 WORKING PRESS bar | 爆破压力 BURSTING PRESS bar | 真空度 VACUUM m H2O | 每卷长度 COIL LENGTH mt |
|-----------------|----------------|----------------|---------------------|----------------------------------|---------------------------------|----------------------------------|------------------------|------------------------------|
| 3/4 | 19 | 28 | 475 | 70 | 20 | 60 | 9 | 60 |
| 1 | 25 | 35.5 | 680 | 80 | 16 | 48 | 9 | 60 |
| | 30 | 40.5 | 770 | 90 | 16 | 48 | 9 | 60 |
| 1 1/4 | 32 | 42.5 | 800 | 100 | 16 | 48 | 9 | 60 |
| | 35 | 47 | 1100 | 115 | 14 | 42 | 9 | 60 |
| 1 1/2 | 38 | 51 | 1200 | 125 | 14 | 42 | 9 | 30 |
| | 40 | 53 | 1220 | 130 | 14 | 42 | 9 | 30 |
| 1 3/4 | 45 | 58 | 1400 | 140 | 12 | 36 | 9 | 30 |
| 2 | 50 | 64 | 1600 | 150 | 12 | 36 | 9 | 30 |
| | 60 | 74 | 2000 | 180 | 12 | 36 | 9 | 30 |
| 2 1/2 | 63 | 77 | 2100 | 190 | 12 | 36 | 9 | 30 |
| | 75 | 91 | 2850 | 190 | 12 | 36 | 9 | 30 |
| 3 | 76 | 92 | 2900 | 210 | 12 | 36 | 9 | 30 |
| | 80 | 96 | 2950 | 220 | 10 | 30 | 9 | 30 |
| 3 1/2 | 90 | 107 | 3500 | 250 | 10 | 30 | 9 | 30 |
| | 100 | 117 | 3950 | 295 | 10 | 30 | 9 | 30 |
| 4 | 102 | 119 | 4000 | 300 | 10 | 30 | 9 | 30 |
| | 120 | 138 | 5300 | 350 | 8 | 24 | 9 | 20 |
| 5 | 127 | 145 | 5800 | 370 | 7 | 21 | 9 | 20 |
| | 150 | 169 | 6800 | 480 | 5 | 15 | 9 | 20 |
| | 152 | 171 | 6850 | 480 | 5 | 15 | 9 | 20 |