

912909 真空导电燃油管 VACUPRESS

OIL PU

双层热塑性 PVC, PU, 丁晴橡胶混合材料, 内嵌镀锌钢丝螺旋, 聚酯纤维加强, 铜丝防静电, 耐磨 PU 外层, 用于抽吸和输送石油、蓝油、柴油、生物柴油。



Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement with copper wire for an anti-static rendering, with outer cover made of anti-abrasive PU, for suction and delivery of oils, blue diesel, diesel, bio diesel.

商品详情

表面平滑度 SMOOTH SURFACE	*****
柔韧性能 FLEXIBILITY	***
耐磨性能 ABRASION RESISTANCE	ISO 4649:<30 mm ³
适用温度范围 TEMPERATURE RANGE	-25°C + 60°C
抗化学物质 CHEMICAL RESISTANCE	tabella PVC 石油
抗压性能 CRUSHING RESISTANCE	***
防静电性能 ANTISTATIC	Resistenza treccia 0,075 OHM/m

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
3	76	90.5	2700	210	10	30	9	30
	80	94.5	2800	220	10	30	9	30
3 1/2	90	106	3250	250	10	30	9	30
4	102	117.5	3700	300	10	30	9	30
	120	137	4750	450	8	24	9	20
5	127	144	5300	480	7	21	9	20
	150	167.5	6300	550	5	15	9	20
6	152	169.5	6350	550	5	15	9	20