

## 912977 IBERFLEX

PVC 软管，内嵌高密度螺旋镀锌钢丝，用于抽吸和输送食品液体。



PVC hose with embedded reduced pitch galvanised steel spiral, for suction and delivery of food liquids.

### 商品详情

表面平滑度 SMOOTH SURFACE	*****
柔韧性能 FLEXIBILITY	****
耐磨性能 ABRASION RESISTANCE	***
适用温度范围 TEMPERATURE RANGE	-5°C + 65°C
抗化学物质 CHEMICAL RESISTANCE	tabella PVC
抗压性能 CRUSHING RESISTANCE	***

符合 CE1935/2004 标准和 UE10/2011 标准规定接触食品的介质需要通过在温度 40°C 分别对 A B C 三种模拟液体进行 24 小时的测试。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
3/8	10	16.2	180	40	10	30	9	30
	12	18.2	190	48	10	30	9	30
	13	19.2	210	52	10	30	9	30
	14	20.2	230	56	10	30	9	30
5/8	16	22.2	260	64	10	30	9	30
	18	25	295	72	9	27	9	30
	20	27	340	80	9	27	9	30

1	25	33	520	100	8.5	25.5	9	30
	30	38.4	630	120	8	24	9	30
1 1/4	32	40.4	660	128	8	24	9	30
	35	43.6	750	140	8	24	9	30
1 1/2	38	47	800	152	8	24	9	30
	40	49.6	950	160	8	24	9	30
1 3/4	45	54.8	1150	180	8	24	9	30
2	50	60.8	1300	200	6	18	9	30
	51	61.8	1330	204	6	18	9	30
	55	66	1500	220	5.5	16.5	9	30
	60	72	1750	240	5.5	16.5	9	30
2 1/2	63	74	1800	252	5.5	16.5	9	30
	70	83.4	2100	280	4.5	13.5	8.5	30
	75	88.4	2250	300	4.5	13.5	8.5	30
	80	92.6	2500	320	3.5	10.5	8.5	30
3 1/2	90	103	2900	360	3.5	10.5	8.5	30
	100	116	3650	400	2.5	7.5	8.5	30
	110	126	3950	440	2.5	7.5	8	20
	120	136	4300	480	2.5	7.5	8	20
	125	141.4	4600	500	2.5	7.5	8	20
	150	169.4	6500	600	2	6	8	20
8	203	223	9000	812	1.5	4.5	8	10