

911034 COLORADO SUPERELASTIC

柔韧 PVC 软管，硬质 PVC 筋骨螺旋，用于抽吸和输送

液体、灌溉系统、下水管道和污水处理。

Flexible PVC hose with rigid PVC spiral, for suction

and delivery of liquids, irrigation systems, sewage drains and cesspits.



商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

耐磨性能

ABRASION RESISTANCE

适用温度范围

TEMPERATURE RANGE

-25°C + 55°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
2	51	62	1200	290	7	21	9	30
2 1/2	63	76.5	1700	360	7	21	9	30
3	76	89.6	2000	450	6	18	9	30
	80	93.4	2200	500	6	18	9	30
	90	103.6	2500	560	6	18	9	30
	100	115	3300	620	4.5	13.5	9	30
4	102	116.6	3300	640	4.5	13.5	9	30
5	127	143.8	4200	860	4.5	13.5	9	30
6	152	171.6	5900	1100	2.5	7.5	9	20
	200	226	10500	1200	2	6	9	15
8	203	229.4	10500	1300	2	6	9	15