

911026 IDRO POOL

PVC 软管, PVC 筋骨螺旋, 作为硬质水管的替代品或

同类产品, 用于 SPA、游泳池的供应循环系统。

PVC hose with PVC spiral, spa-bath,

swimming-pool supply and recirculation as a substitute or alternative to

the rigid hoses.



商品详情:

表面平滑度 SMOOTH SURFACE	*****
柔韧性能 FLEXIBILITY	***
耐磨性能 ABRASION RESISTANCE	****
适用温度范围 TEMPERATURE RANGE	-5°C + 60°C
抗化学物质 CHEMICAL RESISTANCE	tabella PVC
抗压性能 CRUSHING RESISTANCE	****
校对直径 CALIBRATE DIAMETERS	

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	14	20	210	60	7	21	7	30
	15	20.2	180	60	7	21	7	30
5/8	16	21.5	210	65	7	21	7	30
	20	25	250	80	7	21	7	30
	20	25.5	250	80	7	21	7	30
1	25	32	395	100	7	21	7	30

1	25	33	480	100	7	21	7	30
1	25	33.9	500	100	7	21	7	30
	27	33.8	400	110	7	21	7	30
1 1/4	32	40	600	128	7	21	7	30
	35	42.3	550	140	6	18	7	30
	40	48	720	160	6	18	7	30
	40	48.5	730	160	6	18	7	30
	40	48.9	790	160	6	18	7	30
	40	50.3	930	160	6	18	7	30
	42	50	785	160	6	18	7	30
	43	50	680	175	5	15	7	30
2	50	60	1020	200	5	15	7	30
2	50.8	63	1380	210	5	15	7	30
	55	63	1000	220	5	15	7	30
	65	75	1400	260	5	15	7	30