


912905 SUPERFLEX PU LR

COMPATTATO

PU 软管，镀铜钢丝螺旋，用于抽吸和输送粉尘，木屑及粗糙材料。



Polyurethane hose with copper-plated steel spiral, for suction and transport of dusts, chips and abrasive material.

商品详情

表面平滑度 SMOOTH SURFACE	**
柔韧性能 FLEXIBILITY	*****
耐磨性能 ABRASION RESISTANCE	*****
适用温度范围 TEMPERATURE RANGE	-40°C + 90°C
抗化学物质 CHEMICAL RESISTANCE	tabella PU
抗压性能 CRUSHING RESISTANCE	**
压缩系列 COMPACTED VERSION	6/10 mt
抗臭氧 OZONE RESISTANCE	*****

内径 ID Inc	内径 ID mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	螺旋间距 SPIRAL PITCH mm	螺旋直径 SPIRAL mm	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
2	50	0.4	185	13	18	1.2	0.20	6/10
	55	0.4	200	14	18	1.2	0.18	6/10
	60	0.4	220	15	18	1.2	0.16	6/10
2	63	0.4	230	16	18	1.2	0.15	6/10

1/2								
	70	0.4	330	18	18	1.4	0.14	6/10
	75	0.4	350	19	18	1.4	0.10	6/10
	80	0.4	370	20	18	1.4	0.10	6/10
3 1/2	90	0.4	420	22	18	1.4	0.10	6/10
	100	0.4	480	20	23	1.6	0.09	6/10
	110	0.4	520	22	23	1.6	0.09	6/10
	120	0.4	550	24	23	1.6	0.09	6/10
	125	0.4	590	25	23	1.6	0.08	6/10
	130	0.4	610	26	23	1.6	0.08	6/10
	140	0.4	660	28	23	1.6	0.08	6/10
	150	0.5	700	30	30	1.8	0.06	6/10
	160	0.5	750	32	30	1.8	0.06	6/10
	170	0.5	780	34	30	1.8	0.06	6/10
	180	0.5	830	36	30	1.8	0.06	6/10
	200	0.5	920	40	30	1.8	0.05	6/10
	220	0.5	1070	45	30	1.8	0.05	6/10
	250	0.6	1250	50	36	2.0	0.04	6/10
	300	0.6	1500	60	36	2.0	0.03	6/10
	350	0.6	1750	70	36	2.0	0.03	6/10
	400	0.6	2000	80	36	2.0	0.02	6/10
	450	0.6	2300	90	36	2.0	0.01	6/10
	500	0.6	2500	100	36	2.0	0.01	6/10
	600	0.6	3000	120	36	2.0	0.01	6/10