

913002 SUPERFLEX PU

PU 软管，镀锌钢丝螺旋，用于抽吸和输送粉尘、木屑及粗糙材料。

Polyurethane hose with galvanised steel spiral, for suction and transport of dusts, chips and abrasive material.



商品详情

表面平滑度 SMOOTH SURFACE	***
柔韧性能 FLEXIBILITY	****
耐磨性能 ABRASION RESISTANCE	*****
适用温度范围 TEMPERATURE RANGE	-40°C + 90°C
抗化学物质 CHEMICAL RESISTANCE	tabella PU
抗压性能 CRUSHING RESISTANCE	***
抗臭氧 OZONE RESISTANCE	*****

内径 ID Inc	内径 ID mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	螺旋间距 SPIRAL PITCH mm	螺旋直 径 SPIRAL mm	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	40	0.5	180	40	10	1.0	4.50	30
1 3/4	45	0.5	200	45	10	1.0	4.00	30
2	50	0.55	260	50	12	1.2	3.50	30
	60	0.55	300	60	12	1.2	3.00	30
2 1/2	63	0.55	320	63	12	1.2	2.50	30

	70	0.6	420	70	14	1.4	2.50	30
	75	0.6	440	75	14	1.4	2.00	30
	80	0.6	480	80	14	1.4	2.00	30
$\frac{3}{1/2}$	90	0.6	520	90	14	1.4	2.00	30
	100	0.65	660	100	16	1.6	1.50	30
	110	0.65	720	110	16	1.6	1.50	30
	120	0.65	780	120	16	1.6	1.50	30
	125	0.65	800	125	16	1.6	1.50	30
	130	0.65	840	130	16	1.6	1.50	30
	140	0.65	900	140	16	1.6	1.50	30
	150	0.7	1100	150	18	1.8	1.00	30
	160	0.7	1160	160	18	1.8	1.00	30
	170	0.7	1240	170	18	1.8	1.00	30
	180	0.7	1300	180	18	1.8	1.00	30
	200	0.7	1440	200	18	1.8	1.00	30
	220	0.7	1580	220	18	1.8	0.50	15
	250	0.8	1880	250	22	2.0	0.50	15
	300	0.8	2250	300	22	2.0	0.40	15