

913023 SUPERFLEX PU PLUS H

PU 软管，镀锌钢丝螺旋，用于抽吸和输送粉尘、木屑及粗糙材料。



Polyurethane hose with galvanised steel spiral,
for suction and transport of dusts, chips and abrasive material.

商品详情

| | |
|------------------------------|--------------|
| 表面平滑度 SMOOTH SURFACE | ***** |
| 柔韧性能 FLEXIBILITY | *** |
| 耐磨性能 ABRASION RESISTANCE | ***** |
| 适用温度范围 TEMPERATURE RANGE | -40°C + 90°C |
| 抗化学物质 CHEMICAL RESISTANCE | tabella PU |
| 抗压性能 CRUSHING RESISTANCE | *** |
| 抗臭氧 OZONE RESISTANCE | ***** |

符合 CE1935/2004 标准和 UE10/2011 标准规定：接触食品、干燥食品的介质需要通过在温度 40° C 分别对 A B C 三种模拟液进行 24 小时的测试；接触油脂食品介质需通过在温度 40° C 时对模拟液体 D2 进行 24 小时测试，下降系数等于或高于 X/2。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with dry foodstuff and with foodstuff that requires a simulating liquid type A B C, and oily and fatty foodstuff with a reduction coefficient equal or superior to X/2, that require a simulating type D2. Migration tests performed at 40°C for 24 hours.

符合：FDA 21 CFR 177.1680，关于干燥食品的规定。

Complies with FDA 21 CFR 177.1680, for dry foodstuff.

| 内径 ID Inc | 内径 ID mm | 壁厚 WALL THICKNESS mm | 重量 WEIGHT g/m | 弯曲半径 BENDING RADIUS mm | 螺旋间距 SPIRAL PITCH mm | 螺旋直径 SPIRAL mm | 真空度 VACUUM m H2O | 每卷长度 COIL LENGTH mt |
|-----------------|----------------|-------------------------------|---------------------|---------------------------------|----------------------------|----------------------|------------------------|------------------------------|
| 1 1/2 | 38 | 1 | 480 | 75 | 10 | 1.5×1.9 | 7.5 | 30 |
| | 40 | 1 | 520 | 80 | 10 | 1.5×1.9 | 7.0 | 30 |
| 1 3/4 | 45 | 1 | 570 | 90 | 10 | 1.5×1.9 | 6.5 | 30 |
| 2 | 50 | 1 | 630 | 100 | 10 | 1.5×1.9 | 6.0 | 30 |
| | 60 | 1 | 740 | 120 | 10 | 1.5×1.9 | 5.0 | 30 |
| 2 1/2 | 63 | 1 | 770 | 125 | 10 | 1.5×1.9 | 5.0 | 30 |
| | 70 | 1.1 | 880 | 140 | 14 | 1.5×1.9 | 4.5 | 30 |
| 3 | 76 | 1.1 | 940 | 150 | 14 | 1.5×1.9 | 4.0 | 30 |
| | 80 | 1.1 | 1000 | 160 | 14 | 1.5×1.9 | 4.0 | 30 |
| 3 1/2 | 90 | 1.1 | 1100 | 180 | 14 | 1.5×1.9 | 3.5 | 30 |
| | 100 | 1.1 | 1250 | 200 | 14 | 1.5×1.9 | 3.0 | 30 |
| | 120 | 1.1 | 1480 | 240 | 18 | 2.0×2.5 | 2.5 | 30 |
| 5 | 127 | 1.1 | 1580 | 250 | 18 | 2.0×2.5 | 2.5 | 30 |
| | 130 | 1.1 | 1630 | 260 | 18 | 2.0×2.5 | 2.5 | 30 |
| | 140 | 1.1 | 1750 | 280 | 18 | 2.0×2.5 | 2.0 | 30 |
| | 150 | 1.1 | 1840 | 300 | 18 | 2.0×2.5 | 2.0 | 30 |
| | 160 | 1.1 | 2000 | 320 | 18 | 2.0×2.5 | 1.8 | 30 |
| | 200 | 1.1 | 2500 | 400 | 18 | 2.0×2.5 | 1.5 | 30 |
| | 250 | 1.1 | 3800 | 500 | 18 | 2.0×3.0 | 1.0 | 15 |
| | 300 | 1.1 | 4500 | 600 | 18 | 2.0×3.0 | 1.0 | 15 |