

## 912951 SUPERFLEX PU PLUS DX HMR

PU 导电性软管，PU 包裹镀铜钢丝螺旋，根据 ATEX 规定的用于抽吸和输送机器输出的粉尘、颗粒物、液体、蒸汽。



Polyurethane conductive hose with copper-plated steel spiral covered with PU, for suction and delivery of materials in dust or granular form, liquids, vapours supplied with machines required by the ATEX regulation

### 商品详情

表面平滑度  
SMOOTH SURFACE \*\*\*\*\*

柔韧性能  
FLEXIBILITY \*\*

耐磨性能  
ABRASION \*\*\*\*\*  
RESISTANCE

适用温度范围  
TEMPERATURE RANGE -30°C + 90°C

抗化学物质  
CHEMICAL RESISTANCE tabella PU

抗压性能  
CRUSHING \*\*\*\*\*  
RESISTANCE

导电性能  
CONDUCTIVE 根据 ASTM D 257 表面电阻  $\leq 10^4$  Ohm 数值随时间而变化。  
According to the ASTM D 257 Surface resistance  $\leq 10^4$  Ohm Varying value with time.

抗臭氧  
OZONE RESISTANCE \*\*\*\*\*

内径 ID Inc	内径 ID mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	螺旋间距 SPIRAL PITCH mm	螺旋直径 SPIRAL mm	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	40	1.2	390	80	13	1.4×1.8	9.0	15
	50	1.3	580	100	14	1.6×2.0	7.5	15
	60	1.3	680	120	14	1.6×2.0	7.0	15
	70	1.4	850	140	15	1.8×2.2	6.0	15
	76	1.4	-	180	15	1.8×2.2	6.0	15
	100	1.5	1250	200	16	2.0×2.5	5.0	15