

## 913001 SUPERFLEX CALOR

热塑橡胶软管，镀锌钢丝螺旋，用于抽吸、输送气体及酸性蒸汽。



Thermoplastic rubber hose with galvanised steel spiral, for suction and transport of air and acid vapours.

### 商品详情

表面平滑度 SMOOTH SURFACE	***
柔韧性能 FLEXIBILITY	*****
耐磨性能 ABRASION RESISTANCE	**
适用温度范围 TEMPERATURE RANGE	-25°C + 125°C
抗化学物质 CHEMICAL RESISTANCE	tabella TPV
抗压性能 CRUSHING RESISTANCE	***

内径 ID Inc	内径 ID mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	螺旋间距 SPIRAL PITCH mm	螺旋直径 SPIRAL mm	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	40	0.7	200	40	10	1.0	3	30
1 3/4	45	0.7	230	45	10	1.0	3	30
2	50	0.7	280	50	12	1.2	2.5	30
	60	0.7	320	60	12	1.2	2.5	30
2 1/2	63	0.7	340	63	12	1.2	2.5	30
	70	0.7	420	70	14	1.4	2	30
	75	0.7	440	75	14	1.4	2	30
	80	0.7	480	80	14	1.4	1.7	30
3 1/2	90	0.7	520	90	14	1.4	1.7	30
	100	0.7	660	100	16	1.6	1.4	30

	110	0.7	720	110	16	1.6	1.4	30
	120	0.7	780	120	16	1.6	1.2	30
	125	0.7	800	125	16	1.6	1.2	30
	130	0.7	840	130	16	1.6	1	30
	140	0.7	900	140	16	1.6	1	30
	150	0.7	1100	150	18	1.8	0.7	30
	160	0.7	1160	160	18	1.8	0.7	30
	170	0.7	1240	170	18	1.8	0.5	30
	180	0.7	1300	180	18	1.8	0.5	30
	200	0.7	1440	200	18	1.8	0.4	30
	220	0.7	1600	220	18	1.8	0.4	15
	250	0.8	1850	250	22	2.0	0.3	15
	300	0.8	2300	300	22	2.0	0.2	15