

912995 TERMOFLEX 300°C DOUBLE

硅树脂软管 聚酯纤维表层 镀锌钢丝螺旋在两层硅胶间，
 用于抽吸烟雾及热气。 Hose made in silicone coated
 fiberglass with galvanised steel spiral embedded
 between two layers of silicone, for suction of fumes and hot air.



商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

耐磨性能

ABRASION RESISTANCE

适用温度范围

TEMPERATURE RANGE

-85°C + 300°C

抗化学物质

CHEMICAL RESISTANCE

硅胶

SILICONE

抗压性能

CRUSHING RESISTANCE

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
2	51	56	331	51	2.5	7.5	5	4
2 1/2	63	63	415	63	2.4	7.2	4.5	4
	70	75	500	70	2.3	6.9	4.5	4
3	76	81	531	76	2.3	6.9	4	4
	83	87	590	83	2.1	6.3	4	4
3 1/2	89	94	610	89	2.1	6.3	3.95	4
4	102	107	710	102	1.9	5.7	3.05	4
	114	120	845	114	1.6	4.8	2.8	4
	121	127	980	121	1.5	4.5	2.7	4
5	127	133	925	127	1.4	4.2	2.2	4
	140	146	1020	140	1.8	5.4	1.8	4

6	152	158	1200	152	1.7	5.1	1.7	4
	178	189	1430	178	1.2	3.6	1.2	4
8	203	209	1650	203	0.9	2.7	0.9	4
10	254	260	1140	254	0.4	1.2	0.4	4
12	305	311	1580	305	0.2	0.6	0.3	4