

912831 SUPERFLEX PU CHR

PU 软管，镀铜钢丝螺旋，用于抽吸和输送粉尘、木屑及粗糙材料。 Polyurethane hose with copper-plated steel spiral, for suction and transport of dusts, chips and abrasive material.



商品详情

表面平滑度 SMOOTH SURFACE	***
柔韧性能 FLEXIBILITY	*****
耐磨性能 ABRASION RESISTANCE	*****
适用温度范围 TEMPERATURE RANGE	-40°C + 90°C
抗化学物质 CHEMICAL RESISTANCE	tabella PU
抗压性能 CRUSHING RESISTANCE	***
抗臭氧 OZONE RESISTANCE	*****

符合 CE1935/2004 标准和 UE10/2011 标准规定：接触食品、干燥食品的介质需要通过在温度 40° C 分别对 A B C 三种模拟液进行 24 小时的测试；接触油脂食品介质需通过在温度 40° C 时对模拟液体 D2 进行 24 小时测试，下降系数等于或高于 X/2。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with dry foodstuff and with foodstuff that requires a simulating liquid type A B C, and oily and fatty foodstuff with a reduction coefficient equal or superior to X/2, that require a simulating type D2. Migration tests performed at 40°C for 24 hours.

内径 ID Inc	内径 ID mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	螺旋间距 SPIRAL PITCH mm	螺旋直 径 SPIRAL mm	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
1	25	0.3	130	50	7	1.0	0.40	30
	30	0.3	145	60	8	1.0	0.40	30

	35	0.3	160	70	8	1.0	0.28	30
	40	0.35	190	80	8.5	1.0	0.23	30
1 3/4	45	0.35	200	90	9.5	1.0	0.20	30
2	50	0.35	210	100	9.5	1.0	0.18	30
	55	0.35	240	110	9.5	1.0	0.15	30
	60	0.35	250	120	10.5	1.0	0.14	30
2 1/2	63	0.35	260	125	10.5	1.0	0.10	30
	70	0.35	320	140	12.5	1.3	0.10	30
3	76	0.35	360	155	12.5	1.3	0.09	30
	80	0.4	400	160	14	1.3	0.09	30
3 1/2	90	0.4	420	180	14	1.3	0.09	30
	100	0.4	430	200	15	1.3	0.08	30
	110	0.4	460	220	16	1.3	0.08	30
	120	0.4	480	240	16	1.3	0.06	30
	125	0.4	540	250	16	1.3	0.06	30
	130	0.4	580	260	16	1.3	0.06	30
	140	0.4	600	280	16	1.3	0.06	30
	150	0.4	800	300	17	1.6	0.05	30
	160	0.4	820	320	17	1.6	0.05	30
	180	0.4	900	360	20	1.6	0.04	15
	200	0.4	980	400	20	1.6	0.04	15
	250	0.45	1460	500	22	1.8	0.03	15
	300	0.45	1560	600	28	1.8	0.03	15