

915143 RAGNO PU CONDUTTIVO

pu 导电防爆软管

耐磨 PU-热塑橡胶复合软管，聚酯纤维加强，
根据 ATEX 规定用于机器动力的一般气动工
具、喷气枪、喷漆枪。



Antiabrasive polyurethane and thermo-plastic rubber compound hose with polyester yarn reinforcement supplied with machines required by the ATEX regulation, for pneumatic tools in general, airbrushes, paint sprayers.

商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

耐磨性能

ABRASION RESISTANCE

适用温度范围

TEMPERATURE RANGE

-15°C + 60°C

抗化学物质

CHEMICAL RESISTANCE

tabella PU

抗压性能

CRUSHING RESISTANCE

导电性能

CONDUCTIVE

根据 ASTM D 257

表面阻力为 $\leq 10^4$ Ohm

随时间变化

According to the ASTM D 257 Surface resistance $\leq 10^4$ Ohm

Varying value with time.

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS bar	工作压力 WORKING PRESS bar 20°C	工作压力 WORKING PRESS bar 40°C	工作压力 WORKING PRESS bar 60°C	每卷长度 COIL LENGTH mt
1/4	6	10	70	20	20	17	15	100
5/16	8	12	85	22	20	17	15	60
3/8	10	15	130	38	20	17	15	50
1/2	13	19	195	65	20	17	15	30
5/8	16	23	250	60	20	17	15	25