

VOLF-JAMAICA M



商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

*

耐磨性能

ABRASION RESISTANCE

适用温度范围

TEMPERATURE RANGE

-5°C + 60°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

*

| 内径 ID Inc | 内径 ID mm | 外径 OD mm | 重量 WEIGHT g/m | 弯曲半径 BENDING RADIUS bar | 工作压力 WORKING PRESS bar 20°C | 工作压力 WORKING PRESS bar 40°C | 工作压力 WORKING PRESS bar 60°C | 每卷长度 COIL LENGTH mt |
|-----------------|----------------|----------------|---------------------|----------------------------------|---|---|---|------------------------------|
| | 20 | 24 | 150 | 10 | 7 | 4 | 30 | 50/100 |
| 1 | 25 | 29 | 190 | 10 | 7 | 4 | 30 | 50/100 |
| | 30 | 34 | 220 | 10 | 7 | 4 | 30 | 50/100 |
| 1 1/4 | 32 | 36 | 240 | 10 | 7 | 4 | 30 | 50/100 |
| | 35 | 39 | 290 | 10 | 7 | 4 | 30 | 50/100 |
| 1 1/2 | 38 | 42 | 300 | 10 | 7 | 4 | 30 | 50/100 |
| | 40 | 44 | 320 | 10 | 7 | 4 | 30 | 50/100 |
| 1 3/4 | 45 | 49 | 360 | 10 | 7 | 4 | 30 | 50/100 |
| 2 | 51 | 55 | 410 | 10 | 7 | 4 | 30 | 50/100 |
| | 60 | 65 | 550 | 8 | 5 | 3 | 24 | 50/100 |
| 2 1/2 | 63 | 68.5 | 570 | 8 | 5 | 3 | 24 | 50/100 |
| | 70 | 75 | 650 | 8 | 5 | 3 | 24 | 50/100 |
| 3 | 76 | 81 | 700 | 8 | 5 | 3 | 24 | 50/100 |
| | 80 | 85 | 750 | 8 | 5 | 3 | 24 | 50/100 |

| | | | | | | | | |
|-----------------|-----|-----|------|---|---|---|----|--------|
| $\frac{3}{1/2}$ | 90 | 95 | 860 | 8 | 5 | 3 | 24 | 50/100 |
| | 102 | 108 | 1000 | 8 | 5 | 3 | 24 | 50/100 |
| | 110 | 116 | 1150 | 8 | 5 | 3 | 24 | 50/100 |
| 5 | 127 | 133 | 1350 | 6 | 4 | 2 | 18 | 50/100 |
| 6 | 152 | 158 | 1600 | 4 | 3 | 1 | 12 | 50/100 |
| 8 | 204 | 210 | 2400 | 3 | 2 | 1 | 9 | 50 |