

915081 JAMAICA L

柔韧 PVC 软管 ,能平躺放置 ,聚酯纤维加强 ,抗延展性 ,
用于输送常规压缩液体。

Flexible layflat PVC hose, with polyester yarn
reinforcement resistant to elongation, for
pressurised delivery of liquids in general.



商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

*

耐磨性能

ABRASION RESISTANCE

适用温度范围

TEMPERATURE RANGE

-10°C + 60°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

*

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS bar	工作压力 WORKING PRESS bar 20°C	工作压力 WORKING PRESS bar 40°C	工作压力 WORKING PRESS bar 60°C	每卷长度 COIL LENGTH mt
	20	23	135	8.5	7	4	25.5	50/100
1	25	28	155	8.5	7	4	25.5	50/100
1 1/4	32	35	210	8.5	7	4	25.5	50/100
	35	38	220	8.5	7	4	25.5	50/100
1 1/2	38	41	240	8.5	7	4	25.5	50/100
	40	43	250	8.5	7	4	25.5	50/100
1 3/4	45	48	280	6.5	5	2.5	19.5	50/100
2	51	54	320	6.5	5	2.5	19.5	50/100
	60	64	360	6.5	5	2.5	19.5	50/100
2 1/2	63	67.5	420	6.5	5	2.5	19.5	50/100
	70	74	450	5.5	4	2	16.5	50/100
3	76	80	520	5.5	4	2	16.5	50/100
	80	84	580	5.5	4	2	16.5	50/100
3 1/2	90	94	660	5.5	4	2	16.5	50/100
	102	106	720	5.5	4	2	16.5	50/100
	110	115	780	5.5	4	2	16.5	50/100
5	127	132	1130	3	2	0.5	9	50/100
6	152	157	1350	3	2	0.5	9	50/100
8	204	209	2000	2.5	1.5	0.3	7	50