

## 911010 OREGON

PVC 软管 ,硬质 PVC 筋骨螺旋 ,用于抽吸和运输空气、烟、木屑、粉尘、丝状织物及通风设备。



PVC hose with rigid PVC spiral, for suction and ducting of air, fumes, chips, dusts, textile filaments and ventilation.

### 商品详情

表面平滑度 SMOOTH SURFACE	****
柔韧性能 FLEXIBILITY	****
耐磨性能 ABRASION RESISTANCE	***
适用温度范围 TEMPERATURE RANGE	-10°C + 60°C
抗化学物质 CHEMICAL RESISTANCE	tabella PVC
抗压性能 CRUSHING RESISTANCE	***
自灭性材料 MOULD RESISTANCE	UL 94 V2

内径 ID Inc	外径 OD mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	20	0.9	170	20	-	-	5	50
1	25	0.7	185	25	-	-	5	50
	30	0.7	225	30	-	-	5	50
1 1/4	32	0.8	255	32	-	-	5	50
	35	0.8	300	35	-	-	5	50
1 1/2	38	0.8	310	38	-	-	5	50
	40	0.9	330	40	-	-	4	50
1 3/4	45	0.9	370	45	-	-	4	50

2	50	1	440	50	-	-	4	50
	60	1	560	60	-	-	4	50
2 1/2	63	1	600	63.5	-	-	4	50
	70	1	640	70	-	-	4	50
	75	1.1	730	75	-	-	4	50
	80	1.1	790	80	-	-	4	30
3 1/2	90	1.1	950	90	-	-	4	30
	100	1	980	100	-	-	4	30
	110	1.2	1120	110	-	-	4	30
	120	1.3	1300	120	-	-	4	30
	125	1.2	1360	125	-	-	4	30
	130	1.2	1440	130	-	-	4	30
	140	1.2	1600	140	-	-	4	30
	150	1.3	1760	150	-	-	4	30
	160	1.3	1930	160	-	-	4	20
	180	1.3	2300	180	-	-	4	20
	200	1.3	2650	200	-	-	4	20
	250	1.3	3600	250	-	-	4	15
	300	1.5	4500	300	-	-	4	10