

911184 LUISIANA PU ANTISTATICO

PVC 软管，硬质 PVC 筋骨螺旋，PU 内层，内嵌铜线

可防静电，可输送粗糙或带颗粒的材料。

PVC hose with rigid PVC spiral , under layer in

PU and with a copper wire for making the hose antistatic when needed.

Suitable for conveying and carrying abrasive and granular materials



商品详情

表面平滑度 *****

SMOOTH SURFACE

柔韧性能 ***

FLEXIBILITY

耐磨性能 *****

ABRASION RESISTANCE

适用温度范围 -10°C + 60°C

TEMPERATURE RANGE

抗化学物质 tabella PU

CHEMICAL RESISTANCE

抗压性能 *****

CRUSHING RESISTANCE

抗静电性能 Resistenza trefolo 0,075 OHM/m

ANTISTATIC

符合 CE1935/2004 标准和 UE10/2011 标准规定接触食品的介质需要通过在温度 40°C 分别对 A B C 三种模拟液体进行 24 小时的测试。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	30	37.5	450	150	5	15	7	30
1 1/2	38	45	500	190	5	15	7	30
	40	48	630	200	5	15	7	30

2	50	59	900	250	4	12	7	30
	60	70.5	1100	300	4	12	7	30
	70	81	1200	350	4	12	7	30
	76	87	1400	375	3.5	10.5	7	30
	80	91	1500	400	3.5	10.5	7	30
	90	101	1750	450	3.5	10.5	7	30
	100	111	2000	500	3	9	7	30