

## 911075 ARIZONA SUPERELASTIC

PVC 软管，硬质 PVC 筋骨螺旋，用于抽吸和输送

液体，灌溉系统，下水管道及污水处理。

PVC hose with rigid PVC spiral, for suction

and delivery of liquids, irrigation systems,

sewage drains and cesspits.



### 商品详情

表面平滑度

SMOOTH SURFACE

\*\*\*\*\*

柔韧性能

FLEXIBILITY

durezza SHORE A 57 \*\*\*\*\*

耐磨性能

ABRASION RESISTANCE

\*\*\*\*\*

适用温度范围

TEMPERATURE RANGE

-25°C + 55°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

\*\*\*\*\*

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长 度 COIL LENGTH mt
1	25	33.8	500	100	7	21	9	50
1 1/4	32	40.8	600	130	6	18	9	50
1 1/2	38	47	700	150	6	18	9	50
	40	49	740	160	6	18	9	50
1 3/4	45	55	900	180	5.5	16.5	9	50
2	50	61	1050	200	5	15	9	50
	60	71.2	1250	240	4.5	13.5	9	50
2	63	75.5	1390	250	4.5	13.5	9	50

1/2								
	75	88	1700	300	4	12	9	30
3	76	88.8	1700	300	4	12	9	30
	80	92.6	1850	320	3.5	10.5	9	30
3 1/2	89	102.3	2250	360	3.5	10.5	9	30
	90	103.7	2250	360	3.5	10.5	9	30
	100	114.8	2700	400	3	9	9	30
4	102	116.4	2700	400	3	9	9	30
	110	125.5	3100	440	3	9	9	30
	120	136	3600	480	2.5	7.5	9	20
	125	142.1	3900	500	2.5	7.5	9	20
5	127	143.6	3900	510	2.5	7.5	9	20
	130	147	4100	520	2.5	7.5	9	20
	133	150	4200	535	2.5	7.5	9	20
	150	168	5000	600	2	6	9	20
6	152	170.4	5000	610	2	6	9	20
	160	178.8	5600	640	2	6	9	20
	200	226	9500	800	1.5	4.5	9	-
8	203	229.2	9500	800	1.5	4.5	9	-
10	254	283	13500	1000	1.5	4.5	9	-
12	304	335.8	18000	1200	1.5	4.5	9	-